

1 **MOTION-GENERATING ILLUMINATED INFLATABLE**

2 **DECORATION**

3 **BACKGROUND OF THE INVENTION**

4 1. Field of the Invention

5 The present invention relates to an inflatable decoration, and more
6 particularly to an illuminated inflatable decoration that will produce a motion by
7 itself as a passer-by goes through the inflatable decoration.

8 2. Description of Related Art

9 Decorations at exhibitions, fairs etc are often inflatable objects because
10 they are convenient to store and transport when deflated yet can rapidly be
11 expanded to a huge, eye-catching size. An inflatable object in accordance with
12 prior art comprises a gastight inflatable body, a mounting base and an air pump.
13 The inflatable body is mounted on the mounting base and is built into a
14 significant shape, such as a cartoon figure, an inanimate animal-like object or a
15 mascot etc to improve its attraction. The mounting base is placed on the ground
16 to stand the entire inflatable object. The air pump connects to the inflatable body
17 via hollow tubes and pumps ambient air into the inflatable body to swell or
18 distend the inflatable body to become a huge size.

19 However, a conventional inflatable object is static for display and has no
20 capability to provide any illuminated features. Such a conventional inflatable
21 object is going to finally become unattractive to the crowds at the exhibition. In
22 addition, especially in a dark place, the conventional inflatable object is hard to
23 see clearly and cannot attract effectively the attention of people.

24 To overcome the shortcomings, the present invention provides an

1 improved illuminated and dynamic inflatable object to mitigate or obviate the
2 aforementioned problems.

3 SUMMARY OF THE INVENTION

4 The main objective of the invention is to provide an inflatable decoration
5 that will cause attractive motions, such as waving hands, produce blinking lights
6 and sound to attract attention when a person passes through the inflatable
7 decoration such that will increase business promotion and advertisement effects
8 for the inflatable decoration.

9 The inflatable decoration comprises an inflatable body and a dynamic
10 controlling device mounted in the inflatable body. The dynamic controlling
11 device comprises a pulling cord connecting to the inflatable body, a cord driving
12 motor used to change a length of the pulling cord, multiple illuminating elements
13 mounted on the inflatable body to produce lights, a speaker to produce sound, a
14 controller used to control the cord driving motor, the illuminating elements and
15 the speaker to work and a sensor electrically connected to the controller to detect
16 the motion of a passer-by. Therefore, when a person goes through the inflatable
17 decoration, the motion of the person will be detected by the sensor such that the
18 controller actuates the cord driving motor, the illuminating elements and the
19 speaker to cause a motion for the inflatable body, lights for inflatable decoration
20 and sound.

21 Other objectives, advantages and novel features of the invention will
22 become more apparent from the following detailed description when taken in
23 conjunction with the accompanying drawings.

24 BRIEF DESCRIPTION OF THE DRAWINGS

1 Fig. 1 is a front plan view of a motion-generating illuminated inflatable
2 decoration in accordance with the present invention;

3 Fig. 2 is an enlarged plan view of a mounting base of the inflatable
4 decoration in Fig. 1, partially in cross section;

5 Fig. 3 is an exploded perspective view of an air pump of the inflatable
6 decoration in Fig. 1; and

7 Fig. 4 is an operational perspective view of the inflatable decoration in
8 Fig.1, showing a dynamic controlling device actuate the inflatable decoration to
9 waves its hand.

10 DETAILED DESCRIPTION OF PREFERRED EMBODIMENT

11 With reference to Figs. 1 and 2, a motion-generating illuminated
12 inflatable decoration in accordance with the present invention comprises a
13 mounting base (10), an air pump (21), a dynamic controlling device (not
14 numbered), an inflatable body (30) and a power supply (23).

15 The mounting base (10) has an intake air entrance (11) and a sound
16 outlet aperture (12) and comprises a weighted frame (101), a back plate (102)
17 and multiple foldable feet (13). The weighted frame (101) has a top (not
18 numbered), a bottom (not numbered) and a heavy weight to provide a reliable
19 and stable support to the inflatable body (30). The back plate (102) is attached to
20 the top of the weighted frame (101) to fasten and clamp a small portion of the
21 inflatable body (30) and has a top (not numbered). The foldable feet (13) are
22 pivotally mounted on the bottom of the weighted frame (101) such that the
23 mounting base (10) will have a small size to be convenient to store when the
24 foldable feet (13) are folded.

1 The intake air entrance (11) and the sound outlet aperture (12) are
2 respectively defined through the top of the back plate (102), the clamped portion
3 of the inflatable body (30) and the bottom of the weighted frame (101). The
4 inflatable body (30) is mounted on the mounting base (10) and has a bottom (not
5 numbered), an interior periphery (not numbered) with a desired exercising
6 position (not shown), and an inner space (not numbered). In addition, the
7 inflatable body (30) can be made of soft, resilient, light transmittable such as
8 transparent or translucent and gastight materials and can be shaped into any
9 significant figures, such as a human figure (not numbered) with two arms (not
10 numbered) illustrated in the drawings for example. For convenient illustrating
11 purpose only, when the inflatable body (30) is shaped into aforesaid human
12 figure, the desired exercising position is located at one of the arms that tends to
13 make a beckoning gesture for the inflatable body (30). The bottom of the
14 inflatable body (30) is clamped and held between the back plate (102) and
15 weighted frame (101) as previously described.

16 With reference to Figs. 2 and 3, the air pump (21) is a built-in device and
17 is mounted in the inner space of the inflatable body (30) to connect to the intake
18 air entrance (11) of the mounting base (10). The air pump (21) is mounted on the
19 top of the back plate (102) and comprises a hollow body (not numbered), a motor
20 (213), a fan (215), a motor housing (216) and a mounting bracket (214). The
21 mounting bracket (214) is mounted on the top of the back plate (102) and has a
22 through hole (not numbered) aligned with the intake air entrance (11). The
23 hollow body is mounted on the mounting bracket (214), and has a top (not
24 numbered), a bottom (not numbered), an outer edge (not numbered), an air inlet

1 (218), an air outlet (219) and comprises an upper half housing (211) and a lower
2 half housing (212). The upper and the lower half housings (211, 212) connect to
3 each other. The air inlet (218) is defined in the bottom and is aligned with the
4 through hole of the mounting bracket (214). The air outlet (219) is tangentially
5 formed at the outer edge and communicates with the inner space of the inflatable
6 body (30). The motor (213) is mounted on the top of the hollow body and has a
7 shaft (not numbered) that passes through the top of the hollow body and extends
8 into the hollow body. The fan (215) is rotatably mounted in the hollow body,
9 connects to the motor shaft and is rotated by the motor (213) to draw air into the
10 hollow body through the air inlet (218) and force the drawn air out of the hollow
11 body through the air outlet (219) into the inner space of the inflatable body (30).
12 The motor housing (216) is attached to the top of the hollow body to enclose the
13 motor (213).

14 With reference to Figs. 1 and 2, the dynamic controlling device is
15 mounted in the inner space of the inflatable body (30) and comprises a cord
16 driving motor assembly (40), a speaker (41), a pulling cord (42), an illuminated
17 device (not numbered), a sensor (43) and a controller (44) mounted on the top of
18 the back plate (102). The cord driving motor assembly (40) is mounted on the
19 interior periphery of the inflatable body (30) and has a mounting frame (401), a
20 cord driving motor (402) with a shaft (not numbered) and a bobbin (403)
21 attached to the motor shaft. The cord driving motor (402) connects electrically to
22 the controller (44) and is controlled by the controller (44) to rotate in either
23 counterclockwise or clockwise directions or stop the shaft.

24 The pulling cord (42), such as a stainless steel cord interconnects the

1 interior periphery of the inflatable body (30) with the shaft of the cord driving
2 motor (402) and has a distal end (not numbered) and a proximal end (not
3 numbered). The proximal end is wrapped around the bobbin (403) on the shaft of
4 the cord driving motor (402). The distal end is fastened at the desired exercising
5 position of the interior periphery of the inflatable body (30) to pull the desired
6 exercising position to cause a motion for the inflatable body (30), such as waving
7 its hands. Therefore, the pulling cord (42) will cause a motion at the desired
8 exercising position as the cord driving motor (402) rotate the shaft to change the
9 length of the pulling cord (42).

10 The illuminated device is mounted on the interior periphery of the
11 inflatable body (30), connects electrically to the controller (44) and is controlled
12 by the controller (44) to produce lights, such as blinking lights. The illuminated
13 device has multiple illuminating elements (45), such as light bulbs or light
14 emitting diodes (LEDs) that are respectively mounted on the interior periphery
15 of the inflatable body (30) and connect respectively to the controller (44) to
16 produce blinking lights.

17 The sensor (43) electrically connects to the controller (44) and is
18 mounted on the inflatable body (30) at a detectable height with respect to the
19 height of a normal human to detect a person who goes past the inflatable body
20 (30). The power supply (23) is mounted outside the inflatable body (30) to
21 provide an electricity support for the air pump (21) and the controller (44) that
22 actuates the motor (402), the illuminating elements (45) and the speaker (41).

23 Consequently, the foldable feet (13) are spread to stand the inflatable
24 decoration on the ground, then the air pump (21) is started to pump continuously

1 the atmospheric air into the inner space of the inflatable body (30) to swell the
2 inflatable body (30) to become a human shape. Since the air pump (21)
3 continuously pumps the air into the inflatable body (30), the inflatable body (30)
4 will be maintained with a stable shape.

5 With reference to Fig. 4, when a passer-by (not shown) goes through the
6 inflatable decoration and the sensor (43) detects the motion of the passer-by, the
7 controller (44) will actuate the speaker (41) to produce sound, the illuminating
8 elements (45) to produce blinking lights and the cord driving motor (402) to
9 rotate intermittently the bobbin (403) in both directions. The rotation of the
10 bobbin (403) will change simultaneously the length of the pulling cord (42) to
11 make a beckoning gesture for the inflatable body (30). With those visible
12 blinking lights, sounds and dynamic postures of the inflatable decoration, the
13 inflatable decoration in accordance with the present invention becomes more
14 decorative and attractive than a prior one. For an exhibition or a children's
15 playground, the inflatable decoration in accordance with the present invention
16 provide multiple effects for business advertisements and promotions.

17 Even though numerous characteristics and advantages of the present
18 invention have been set forth in the foregoing description, together with details
19 of the structure and function of the invention, the disclosure is illustrative only,
20 and changes may be made in detail, especially in matters of shape, size, and
21 arrangement of parts within the scope of the appended claims.